

Light Specifications

Technical sheet: CLS16

Project name:

Project number:

Technical Description: Covelight Superior RGBW



Can be used with

- Profile Ref. CLS141006 (plastic profile with 2M)
- CLS LDV-45 DMX dimmer
- Zense controller

Led

Reference : *

Type : LEDstrip RGBW

Quantity of LED : 72 x LED p/m

Angle : N/A

Voltage : Max. 16W/M

Light consumption : 24VDC**

Lifetime : Min. 10.000 Hours

Module

Size : 4mm x 14mm

LED distance : 28mm

Depth : N/A

Material of module : PVC with silicone

Colour : RGBW

Weight : 80gr

Pression : N/A

Cable : 2 x 1M

Rotation : N/A

Dimmable : DMC LDV45 dimmer

Driver : Exclusive

Protection : IP44***

Warranty : 1 Year

Reference*	Colour	LED distance	LEDs	Cut	Watt
CLS141201	RGBW - 5M	28mm	30/meter	Every 16,5cm	Max. 16W p/m

Note:

**Use with transformer 24VDC

***With 2 IP68 connections, the covelight becomes IP68

Supplier

Chainlight Lighting Systems
Rua Fernão Vilarinho lote 15 BI B, loja 6
8600-315 Lagos - Portugal

Tel: +351 282778128

www.chainlight.pt E-mail: info@chainlight.eu