

Light Specifications

Technical sheet: CLS26


Project name:

Project number:

Technical Description: Hylo Up & Downlighter



Can be used with • Extended bracket



Led

Reference	: CLS-H1
Type	: Wall projector
Quantity of LED	: 16x LED Luxeon Cree
Angle	: 8°, 12°, 30°, 61°, 80° or 12x46°
Voltage	: 180-264VAC
Light consumption	: Max. 20VA
Lifetime	: Min. 50.000 Hours
Dimmer	: No

Module

Size	: 99mm x 99mm x 200mm
Depth	: No
Cut-out	: N/A
Material of module	: Anodized Aluminium
Colour	: Aluminium
Weight	: 2,30gr
Pression	: N/A
Cable	: No
Rotation	: N/A
Driver	: Inclusive
Protection	: IP67
Warranty	: 3 Years
Energy class	: A

Colour	Kelvin	Lumen	Watt
Extra Warm White	2700K	1309Lm	20W
Warm White	3000K	1417Lm	20W
Natural White	4000K	1976Lm	20W
Cool White	5000K	2200Lm	20W
Cool White	6500K	2650Lm	20W
Amber			20W

Note: Optional colours: use with lenses amber, red, green or blue

Supplier

Chainlight Lighting Systems
Rua Fernão Vilarinho lote 15 Bl B, loja 6
8600-315 Lagos - Portugal

Tel: +351 282778128
www.chainlight.pt E-mail: info@chainlight.eu