

Light Specifications

Technical sheet: CLS29

Project name:

Project number:

Technical Description: Luxo 6 Basic





Can be used with • Difuse filter ref. CLS111098

Led

Reference : CLS-L-6-1-03-2-B-3
Type : Downlighter
Quantity of LED : 6x LED Cree
Angle : 25°, 40°, 60° or 120°
Voltage : Max. 700mA
Light consumption : 16W
Lifetime : Min. 50.000 Hours
Dimmable : Depends of driver

Module

Size : Ø140mm x 62,8mm
Depth : 100mm
Cut-out : Ø127mm
Material of module : Brushed Aluminium
Colour : Brushed Aluminium
Weight : 460gr
Pression : N/A
Cable : 150cm
Rotation :  360°  40°
Driver : Exclusive
Protection : IP40
Warranty : 3 Years
Energy class : A

Colour	Kelvin	Lumen
Extra Warm White	2700K	530Lm
Warm White	3000K	600Lm
Natural White	4000K	880Lm

Note: Plug & Play System

Supplier

Chainlight Lighting Systems
Rua Fernão Vilarinho lote 15 Bl B, loja 6
8600-315 Lagos - Portugal

Tel: +351 282778128
www.chainlight.pt E-mail: info@chainlight.eu