

Light Specifications

Technical sheet: CLS25

Project name:
Project number:

Technical Description: Revo Compact Inground Series



Can be used with

Led

| | |
|-------------------|------------------------------------|
| Reference | : CLS-RC-I |
| Type | : Groundspot |
| Quantity of LED | : 4x LED Luxeon Cree |
| Angle | : 8°, 12°, 30°, 61°, 80° or 12x46° |
| Voltage | : 180-264VAC |
| Light consumption | : Max. 10W |
| Lifetime | : Min. 50.000 Hours |
| Dimmable | : No |

Module

| | |
|--------------------|--------------------------|
| Size | : Ø150mm x 205mm |
| Depth | : 205mm |
| Cut-out | : Ø14,6cm - depth 19,8cm |
| Material of module | : Anodized Aluminium |
| Colour | : Aluminium |
| Weight | : 2,15kg |
| Pression | : 15kg/cm ₂ |
| Cable | : 300cm |
| Rotation | : 360° |
| Driver | : Inclusive |
| Protection | : IP67 |
| Warranty | : 3 Years |
| Energy class | : A |

| Colour | Kelvin | Lumen | Watt |
|------------------|--------|-------|------|
| Extra Warm White | 2700K | 646Lm | 10W |
| Warm White | 3000K | 666Lm | 10W |
| Natural White | 4000K | 788Lm | 10W |
| Cool White | 5000K | 514Lm | 10W |
| Amber | | | 10W |

Note: Optional colours: use with lenses amber, red, green or blue

Supplier

Chainlight Lighting Systems
Rua Fernão Vilarinho lote 15 Bl B, loja 6
8600-315 Lagos - Portugal

Tel: +351 282778128
www.chainlight.pt E-mail: info@chainlight.eu