

Light Specifications

Technical sheet: CLS3

Project name:

Project number:

Technical Description: Ultima



Can be used with

Led

Reference	: CLS-U
Type	: Downlighter
Quantity of LED	: 16x LED Luxeon Cree
Angle	: 8°, 12°, 30°, 60° or 12x46°
Voltage	: Max. 700mA
Light consumption	: Max. 20W
Lifetime	: Min. 50.000 Hours
Dimmable	: 1-10 Volt or Phase

Module

Size	: 180mm x 180mm x 40mm
Cut-out complete recess.	: 136mm x 136mm
Cut-out partly recessed	: 82mm
Material of module	: PC / ABS
Colour	: *
Weight	: 450gr
Pression	: N/A
Cable	: 150cm
Rotation	: N/A
Driver	: Inclusive
Protection	: IP20
Warranty	: 3 Years
Energy class	: A

Colour	Kelvin	Lumen
Extra Warm White	2700K	1221Lm
Warm White	3000K	1427Lm
Natural White	4000K	2176Lm
Cool White	5000K	2550Lm

Possible applications:



Built-in complete recessed



Built in with side glow option
partly recessed

Note: *Colours front plate: white, black, gray, transparent, red, green or blue
*Colours back plate: white, black, gray or transparent

Supplier

Chainlight Lighting Systems
Rua Fernão Vilarinho lote 15 BI B, loja 6
8600-315 Lagos - Portugal

Tel: +351 282778128
www.chainlight.pt E-mail: info@chainlight.eu